

View Online at https://aerobasegroup.com/nsn/5915-01-262-4770

Overall Length:
7.760 inches
Body Length:
5.560 inches
Body Outside Diameter:
2.270 inches
Vibration Resistance Range In Hertz:
+10.0/+2000.0
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Power Line Frequency Rating Per Function In Hertz:
400.0 blank
Operating Current Rating Per Function In Amps:
30.0 blank
Maximum Voltage Drop Per Function:
1.15 volts ac blank and 1.15 volts dc blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Maximum Tempurature Rise:
35.0 degrees celsius
Mounting Facility Screw Thread Series Designator:
Unef
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
1 threaded bushing
Functional Terminal Type And Quantity:
1 threaded stud output 2nd function
Operating Voltage Rating And Type Per Function:
115.0 volts ac blank and 400.0 volts dc blank
Thread Size:
1.125 inches
Body Material:
Metal
Maximum Dielectric Withstanding Dc Voltage:
1.0 kilovolts at sea level
Style Designator:
Round terminal/terminals on opposite surfaces



## Test Data Document:

81349-mil-f-15733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-f-15733/73 government specification

## Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

Fiig:

A047b0