

View Online at <https://aerobasegroup.com/nsn/5915-01-263-5948>

**Overall Length:**

5.000 inches

**Body Length:**

4.000 inches

**Body Width:**

2.000 inches

**Body Height:**

1.500 inches

**Unthreaded Mounting Hole Diameter:**

0.213 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

4.500 inches

**Vibration Resistance Range In Hertz:**

+10.0/+500.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.500 inches

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Average Life Rating In Hours:**

1000.0

**Source Impedance Rating Per Function:**

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

**Load Impedance Per Function:**

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

**Power Line Frequency Rating Per Function In Hertz:**

60.0 1st radio interference 60.0 2nd radio interference

**Operating Current Rating Per Function In Amps:**

3.0 1st radio interference 3.0 2nd radio interference

**Maximum Voltage Drop Per Function:**

1.2 volts ac 1st radio interference 1.2 volts ac 2nd radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference

**Maximum Temperature Rise:**

25.0 degrees celsius

**Full Load Insertion Loss Frequencies In Megahertz:**

0.0 and 0.1 and 1.0 and 10.0 and 100.0 and 1000.0

**Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:**

3.0 and 30.0 and 30.0 and 30.0 and 30.0 and 30.0

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Features Provided:**

Shock resistant and nut

**Functional Terminal Type And Quantity:**

2 threaded stud input 1st function 2 threaded stud output 2nd function 1 threaded stud ground 3rd function

**Operating Voltage Rating And Type Per Function:**

120.0 volts ac 1st radio interference 1st function 120.0 volts ac 2nd radio interference 2nd function

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

336.0 volts at sea level

**Special Features:**

Two filtered functions

**Unpackaged Unit Weight:**

5.000 pounds

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0