

View Online at <https://aerobasegroup.com/nsn/5915-01-263-6010>

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.000 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.312 inches

**Reference Frequency Per Function:**

80.0 megahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Input Terminal Manufacturer Code:**

14482

**Input Terminal Identification:**

Sma-plug

**Output Terminal Manufacturer Code:**

14482

**Output Terminal Identification:**

Sma-receptacle

**Voltage Standing Wave Ratio Per Function:**

1.5 blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 threaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

0.5 blank

**Functional Terminal Type And Quantity:**

1 connector, receptacle output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

1.00 hertz blank and 160.00 megahertz blank and 660.00 megahertz blank and 1.16 gigahertz blank

**Thread Size:**

0.112 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.00 hertz blank and 160.00 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

0.5 blank and 0.5 blank and 60.0 blank and 60.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

1.0 hertz blank and 160.0 megahertz blank

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0