

View Online at <https://aerobasegroup.com/nsn/5915-01-263-6010>

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.312 inches

Reference Frequency Per Function:

80.0 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Input Terminal Manufacturer Code:

14482

Input Terminal Identification:

Sma-plug

Output Terminal Manufacturer Code:

14482

Output Terminal Identification:

Sma-receptacle

Voltage Standing Wave Ratio Per Function:

1.5 blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

0.5 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 160.00 megahertz blank and 660.00 megahertz blank and 1.16 gigahertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

1.00 hertz blank and 160.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

0.5 blank and 0.5 blank and 60.0 blank and 60.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

1.0 hertz blank and 160.0 megahertz blank

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0