

View Online at https://aerobasegroup.com/nsn/5915-01-264-2871

| Overall Length: |
|---|
| 1.117 inches |
| Body Length: |
| 0.550 inches |
| Body Outside Diameter: |
| 1.090 inches |
| Vibration Resistance Range In Hertz: |
| +10.0/+2000.0 |
| Operating Tempurature Range: |
| -55.0/+85.0 degrees celsius |
| Average Life Rating In Hours: |
| 1000.0 |
| Source Impedance Rating Per Function: |
| 50.0 ohms blank |
| Load Impedance Per Function: |
| 50.0 ohms blank |
| Operating Current Rating Per Function In Amps: |
| 0.06 blank |
| Principal Circuitry Type Per Function: |
| Inductance-capacitance, mounting end blank |
| Mounting Facility Screw Thread Series Designator: |
| Unf |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Type And Quantity: |
| 1 threaded bushing |
| Functional Terminal Type And Quantity: |
| 1 tab, solder lug output 2nd function |
| Operating Voltage Rating And Type Per Function: |
| 50.0 volts dc blank |
| Thread Size: |
| 0.250 inches |
| Body Material: |
| Metal |
| Maximum Dielectric Withstanding Dc Voltage: |
| 200.0 volts at sea level |
| Body Surface Treatment: |
| Tin |
| Unpackaged Unit Weight: |
| 8.0 grams |
| Style Designator: |
| Round terminal/terminals on opposite surfaces |

Radio Frequency Interference Filter - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0