

View Online at <https://aerobasegroup.com/nsn/5915-01-267-2822>

**Body Length:**

1.120 inches

**Body Width:**

2.000 inches

**Body Height:**

2.500 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.500 inches

**Vibration Resistance Range In Hertz:**

+5.0/+55.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.625 inches

**Operating Temperature Range:**

-0.0/+70.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**End Application:**

Combat control acoustic an/bsy-1

**Source Impedance Rating Per Function:**

50.0 ohms 2nd radio interference

**Load Impedance Per Function:**

50.0 ohms 2nd radio interference

**Power Line Frequency Rating Per Function In Hertz:**

60.0 2nd radio interference

**Operating Current Rating Per Function In Amps:**

2.0 1st radio interference

**Maximum Voltage Drop Per Function:**

1.1 volts ac 2nd radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 2nd radio interference

**Maximum Temperature Rise:**

35.0 degrees celsius

**Average Power Rating Per Function:**

2.0 watts 1st radio interference

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded stud

**Features Provided:**

Shock resistant

**Functional Terminal Type And Quantity:**

2 threaded stud output 2nd function

**Operating Voltage Rating And Type Per Function:**

115.0 volts ac 2nd radio interference 2nd function

**Thread Size:**

0.112 inches

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

2.5 kilovolts at sea level

**Unpackaged Unit Weight:**

5.000 pounds

**Precious Material And Location:**

Connector contact surfaces gold

**Precious Material:**

Gold

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0