

View Online at <https://aerobasegroup.com/nsn/5915-01-267-2822>

Body Length:

1.120 inches

Body Width:

2.000 inches

Body Height:

2.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.500 inches

Vibration Resistance Range In Hertz:

+5.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.625 inches

Operating Temperature Range:

-0.0/+70.0 degrees celsius

Average Life Rating In Hours:

10000.0

End Application:

Combat control acoustic an/bsy-1

Source Impedance Rating Per Function:

50.0 ohms 2nd radio interference

Load Impedance Per Function:

50.0 ohms 2nd radio interference

Power Line Frequency Rating Per Function In Hertz:

60.0 2nd radio interference

Operating Current Rating Per Function In Amps:

2.0 1st radio interference

Maximum Voltage Drop Per Function:

1.1 volts ac 2nd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 2nd radio interference

Maximum Temperature Rise:

35.0 degrees celsius

Average Power Rating Per Function:

2.0 watts 1st radio interference

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Features Provided:

Shock resistant

Functional Terminal Type And Quantity:

2 threaded stud output 2nd function

Operating Voltage Rating And Type Per Function:

115.0 volts ac 2nd radio interference 2nd function

Thread Size:

0.112 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

2.5 kilovolts at sea level

Unpackaged Unit Weight:

5.000 pounds

Precious Material And Location:

Connector contact surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0