

View Online at <https://aerobasegroup.com/nsn/5915-01-269-0884>

Overall Length:

2.450 inches

Body Length:

1.950 inches

Body Width:

0.500 inches

Body Height:

0.400 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.778 inches

Vibration Resistance Range In Hertz:

+5.0/+2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.328 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

End Application:

F16aircombfit

Reference Frequency Per Function:

500.0 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Input Terminal Manufacturer Code:

12436

Input Terminal Identification:

Sma-receptacle

Output Terminal Manufacturer Code:

12436

Output Terminal Identification:

Sma-receptacle

Voltage Standing Wave Ratio Per Function:

1.5 blank

Average Power Rating Per Function:

1.0 watts blank

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

300.00 megahertz blank and 400.00 megahertz blank and 600.00 megahertz blank and 800.00 megahertz blank

Thread Size:

0.060 inches

Body Material:

Metal

Frequency Band Width Per Function:

400.00 megahertz blank and 600.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

45.0 blank and 3.0 blank and 3.0 blank and 45.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

400.0 megahertz blank and 600.0 megahertz blank

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0