

View Online at <https://aerobasegroup.com/nsn/5915-01-273-2085>

Overall Length:

1.295 inches

Body Length:

0.603 inches

Body Outside Diameter:

0.416 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Power Line Frequency Rating Per Function In Hertz:

400.0 blank

Operating Current Rating Per Function In Amps:

2.0 blank

Maximum Voltage Drop Per Function:

0.13 volts ac blank and 1.5 volts dc blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Maximum Temperature Rise:

40.0 degrees celsius

Full Load Insertion Loss Frequencies In Megahertz:

0.0 and 0.1 and 1.0 and 10.0 and 100.0 and 1000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

7.0 and 13.0 and 10.0 and 30.0 and 67.0 and 70.0

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

1 threaded bushing

Functional Terminal Type And Quantity:

1 tab, solder lug input 1st function 1 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

250.0 volts at sea level

Operating Voltage Rating And Type Per Function:

125.0 volts ac blank and 150.0 volts dc blank

Thread Size:

0.250 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

300.0 volts at sea level

Body Surface Treatment:

Tin

Unpackaged Unit Weight:

48.0 grams

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0