

View Online at <https://aerobasegroup.com/nsn/5915-01-273-4155>

**Vibration Resistance Range In Hertz:**

+0.0/+500.0

**Operating Temperature Range:**

-0.0/+50.0 degrees celsius

**Reference Frequency Per Function:**

277.5 megahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Voltage Standing Wave Ratio Per Function:**

1.5 blank

**Average Power Rating Per Function:**

1.0 watts blank

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

3 terminal

**Insertion Loss At Reference Frequency Per Function In Decibels:**

1.0 blank

**Functional Terminal Type And Quantity:**

1 pin output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

1.00 hertz blank and 555.00 megahertz blank and 777.00 megahertz blank and 1.11 gigahertz blank

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.00 hertz blank and 555.00 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 3.0 blank and 35.0 blank and 70.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

1.0 hertz blank and 555.0 megahertz blank

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0