NSN 5915-01-273-7966

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-273-7966

Overall	Length:

1.510 inches

Overall Height:

0.400 inches

Body Length:

0.750 inches

Body Width:

0.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.630 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.380 inches

Operating Tempurature Range:

-20.0/+85.0 degrees celsius

Reference Frequency Per Function:

152.5 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Input Terminal Manufacturer Code:

50140

Input Terminal Identification:

Sma-jack

Output Terminal Manufacturer Code:

50140

Output Terminal Identification:

Sma-jack

Voltage Standing Wave Ratio Per Function:

1.5 blank

Average Power Rating Per Function:

1.0 watts blank

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

0.75 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

NSN 5915-01-273-7966

Low Pass Filter - Page 2 of 2



Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 305.00 megahertz blank and 518.50 megahertz blank and 1.037 gigahertz blank

Thread Size:

0.060 inches

Body Material:

Metal

Frequency Band Width Per Function:

1.00 hertz blank and 305.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 3.0 blank and 40.0 blank and 40.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

1.0 hertz blank and 305.0 megahertz blank

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0