## NSN 5915-01-275-0774

70.0 millimeters **Body Length:** 50.0 millimeters **Body Width:** 20.0 millimeters **Body Height:** 



Band Pass-band Suppression Filter - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5915-01-275-0774 **Overall Length:** 

| 14.0 millimeters   |
|--|
| Unthreaded Mounting Hole Diameter:   |
| 3.2 millimeters  |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 60.0 millimeters   |
| Operating Tempurature Range:   |
| -32.0/+85.0 degrees celsius  |
| End Application:   |
| 5895-01-205-6148 receiver-excite   |
| Source Impedance Rating Per Function:  |
| 50.0 ohms blank  |
| Load Impedance Per Function:   |
| 50.0 ohms blank  |
| Principal Circuitry Type Per Function:                                       |
| Inductance-capacitance blank   |
| Input Terminal Manufacturer Code:  |
| 80063  |
| Input Terminal Identification:   |
| Smb-receptacle   |
| Output Terminal Manufacturer Code:   |
| 80063  |
| Output Terminal Identification:  |
| Smb-receptacle   |
| Inclosure Type:  |
| Encased  |
| Mounting Facility Type And Quantity:   |
| 2 unthreaded hole  |
| Insertion Loss At Reference Frequency Per Function In Decibels:              |
| 3.0 blank  |
| Frequency Band Width Per Function:   |
| 77.00 megahertz blank and 105.00 megahertz blank                             |
| Style Designator:  |
| Rectangular terminal/terminals on opposite surfaces                          |
| Shelf Life:  |
| N/a  |
|  |
|  |

## NSN 5915-01-275-0774

Band Pass-band Suppression Filter - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A047b0