NSN 5915-01-276-0629

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-276-0629

Overall Length:

Between 0.729 inches and 0.761 inches

Mounting Slot Width:

Between 0.125 inches and 0.132 inches

Body Outside Diameter:

0.062 inches

Operating Tempurature Range:

-65.0/+125.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms 4th radio interference

Load Impedance Per Function:

50.0 ohms 5th radio interference

Power Line Frequency Rating Per Function In Hertz:

60.0 3rd radio interference

Operating Current Rating Per Function In Amps:

5.0 3rd radio interference

Maximum Voltage Drop Per Function:

60.0 millivolts dc 6th radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 6th radio interference

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 slot

Functional Terminal Type And Quantity:

55 friction w/grounding strap and pin output 2nd function

Operating Voltage Rating And Type Per Function:

80.0 volts ac 1st radio interference 1st function

Maximum Dielectric Withstanding Dc Voltage:

200.0 volts at sea level

Body Surface Treatment:

Gold

Special Features:

55 filtered pin contacts

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Style Designator:

Round terminal/terminals on opposite surface

Specification Data:

13499-371-9037-010 manufacturers specification control

NSN 5915-01-276-0629

Radio Frequency Interference Filter - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0