

View Online at <https://aerobasegroup.com/nsn/5915-01-276-1157>

Overall Height:

0.747 inches

Body Length:

2.740 inches

Body Width:

0.500 inches

Body Height:

0.619 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.492 inches and 1.508 inches

Operating Temperature Range:

-32.0/+85.0 degrees celsius

End Application:

5895-01-205-6148 receiver-excite

Reference Frequency Per Function:

501.725 kilohertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 terminal

Insertion Loss At Reference Frequency Per Function In Decibels:

7.0 blank

Functional Terminal Type And Quantity:

2 pin ground 3rd function

Specified Frequencies Of Discrimination Per Function:

499.60 kilohertz blank and 500.30 kilohertz blank and 503.15 kilohertz blank and 504.40 kilohertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

500.30 kilohertz blank and 503.15 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 3.0 blank and 3.0 blank and 60.0 blank

Maximum Dielectric Withstanding Dc Voltage:

100.0 volts at sea level

Style Designator:

Rectangular terminal/terminals on one surface

Specification Data:

80063-a3023936-1 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0