## NSN 5915-01-291-2820

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-291-2820

**Overall Height:** 

Between 1.090 inches and 1.170 inches

**Body Length:** 

Between 1.230 inches and 1.270 inches

**Body Width:** 

Between 1.230 inches and 1.270 inches

**Body Height:** 

Between 0.860 inches and 0.900 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

**Operating Tempurature Range:** 

+0.0/+50.0 degrees celsius

**Reference Frequency Per Function:** 

1.0 kilohertz blank

**Source Impedance Rating Per Function:** 

2.0 kilohms blank

**Load Impedance Per Function:** 

2.0 kilohms blank

**Principal Circuitry Type Per Function:** 

Inductance-capacitance blank

**Mounting Facility Screw Thread Series Designator:** 

Unc

**Inclosure Type:** 

Encapsulated or encased

Mounting Facility Type And Quantity:

1 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

1 0 blank

**Functional Terminal Type And Quantity:** 

2 pin ground 3rd function

**Specified Frequencies Of Discrimination Per Function:** 

1.00 hertz blank and 3.50 kilohertz blank and 4.125 kilohertz blank and 6.00 kilohertz blank

Thread Size:

0.138 inches

**Frequency Band Width Per Function:** 

1.00 hertz blank and 3.50 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 3.0 blank and 40.0 blank and 40.0 blank

**Special Features:** 

Altered item

**Style Designator:** 

Rectangular terminal/terminals on one surface

## NSN 5915-01-291-2820

Low Pass Filter - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0