NSN 5915-01-291-6351

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-291-6351

Overa	II Le	ngth:

Between 0.854 inches and 0.878 inches

Body Outside Diameter:

0.062 inches

Unthreaded Mounting Hole Diameter:

Between 0.126 inches and 0.132 inches

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

End Application:

F/tf-15a acft

Source Impedance Rating Per Function:

50.0 ohms 4th radio interference

Load Impedance Per Function:

50.0 ohms 5th radio interference

Operating Current Rating Per Function In Amps:

5.0 3rd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 6th radio interference

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 unthreaded hole

Features Provided:

Shock resistant

Functional Terminal Type And Quantity:

13 friction w/grounding strap and pin output 2nd function

Operating Voltage Rating And Type Per Function:

200.0 volts dc 4th radio interference 4th function

Maximum Dielectric Withstanding Dc Voltage:

500.0 volts at sea level

Special Features:

13 filtered contacts

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Style Designator:

Round terminal/terminals on opposite surface

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5915-01-291-6351

Radio Frequency Interference Filter - Page 2 of 2



Demilitarization:

No

Fiig:

A047b0