

View Online at <https://aerobasegroup.com/nsn/5915-01-291-7699>

**Overall Length:**

Between 47.0 millimeters and 49.0 millimeters

**Overall Height:**

Between 56.6 millimeters and 59.6 millimeters

**Body Length:**

Between 29.5 millimeters and 30.5 millimeters

**Body Width:**

Between 20.0 millimeters and 21.4 millimeters

**Body Height:**

Between 37.0 millimeters and 39.0 millimeters

**Unthreaded Mounting Hole Diameter:**

3.3 millimeters

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 39.5 millimeters and 40.5 millimeters

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Operating Temperature Range:**

-25.0/+55.0 degrees celsius

**End Application:**

6625-01-170-6878

**Source Impedance Rating Per Function:**

50.0 ohms 2nd radio interference

**Load Impedance Per Function:**

50.0 ohms 2nd radio interference

**Power Line Frequency Rating Per Function In Hertz:**

60.0 2nd radio interference

**Operating Current Rating Per Function In Amps:**

3.0 2nd radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 2nd radio interference

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Functional Terminal Type And Quantity:**

2 tab, solder lug output 2nd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

1.5 kilovolts at sea level

**Operating Voltage Rating And Type Per Function:**

250.0 volts ac 2nd radio interference 2nd function

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

1.414 kilovolts at sea level

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0