

View Online at <https://aerobasegroup.com/nsn/5915-01-291-7699>

Overall Length:

Between 47.0 millimeters and 49.0 millimeters

Overall Height:

Between 56.6 millimeters and 59.6 millimeters

Body Length:

Between 29.5 millimeters and 30.5 millimeters

Body Width:

Between 20.0 millimeters and 21.4 millimeters

Body Height:

Between 37.0 millimeters and 39.0 millimeters

Unthreaded Mounting Hole Diameter:

3.3 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 39.5 millimeters and 40.5 millimeters

Vibration Resistance Range In Hertz:

+10.0/+55.0

Operating Temperature Range:

-25.0/+55.0 degrees celsius

End Application:

6625-01-170-6878

Source Impedance Rating Per Function:

50.0 ohms 2nd radio interference

Load Impedance Per Function:

50.0 ohms 2nd radio interference

Power Line Frequency Rating Per Function In Hertz:

60.0 2nd radio interference

Operating Current Rating Per Function In Amps:

3.0 2nd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 2nd radio interference

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 unthreaded hole

Functional Terminal Type And Quantity:

2 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

1.5 kilovolts at sea level

Operating Voltage Rating And Type Per Function:

250.0 volts ac 2nd radio interference 2nd function

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

1.414 kilovolts at sea level

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0