NSN 5915-01-292-3365

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-292-3365

Overall Length:

7.460 inches

Body Length:

Between 5.440 inches and 5.560 inches

Body Outside Diameter:

1.770 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Power Line Frequency Rating Per Function In Hertz:

400.0 blank

Operating Current Rating Per Function In Amps:

20.0 blank

Maximum Voltage Drop Per Function:

1.15 volts ac blank and 1.15 volts dc blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Maximum Tempurature Rise:

35.0 degrees celsius

Mounting Facility Screw Thread Series Designator:

Unef

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

1 threaded bushing

Functional Terminal Type And Quantity:

1 threaded stud input 1st function1 threaded stud output 2nd function

Operating Voltage Rating And Type Per Function:

115.0 volts ac blank and 400.0 volts dc blank

Thread Size:

0.750 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

1.0 kilovolts at sea level

Style Designator:

Round terminal/terminals on opposite surfaces

NSN 5915-01-292-3365

Radio Frequency Interference Filter - Page 2 of 2



Test Data Document:

81349-mil-f-15733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-f-15733/73 governme	ent specification
-------------------------------	-------------------

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0