

View Online at <https://aerobasegroup.com/nsn/5915-01-294-1202>

**Overall Length:**

Between 1.203 inches and 1.222 inches

**Body Length:**

Between 0.600 inches and 0.620 inches

**Body Outside Diameter:**

Between 0.100 inches and 0.103 inches

**Operating Temperature Range:**

-55.0/+150.0 degrees celsius

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Power Line Frequency Rating Per Function In Hertz:**

400.0 blank

**Operating Current Rating Per Function In Amps:**

5.0 blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Full Load Insertion Loss Frequencies In Megahertz:**

0.0 and 27.3 and 100.0 and 1000.0

**Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:**

3.0 and 3.0 and 13.0 and 15.0

**Inclosure Type:**

Encased

**Functional Terminal Type And Quantity:**

1 friction w/grounding strap and pin input 1st function

**Operating Voltage Rating And Type Per Function:**

125.0 volts ac blank and 200.0 volts dc blank

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

600.0 volts at sea level

**Body Surface Treatment:**

Gold

**Precious Material And Location:**

External surfaces gold

**Precious Material:**

Gold

**Style Designator:**

Round terminal/terminals on opposite surface

**Specification Data:**

K0656-7057-2000 manufacturers source control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0