

View Online at https://aerobasegroup.com/nsn/5915-01-294-1202

Overall Length: Between 1.203 inches and 1.222 inches **Body Length:** Between 0.600 inches and 0.620 inches **Body Outside Diameter:** Between 0.100 inches and 0.103 inches **Operating Tempurature Range:** -55.0/+150.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank **Power Line Frequency Rating Per Function In Hertz:** 400.0 blank **Operating Current Rating Per Function In Amps:** 5.0 blank **Principal Circuitry Type Per Function:** Inductance-capacitance blank Full Load Insertion Loss Frequencies In Megahertz: 0.0 and 27.3 and 100.0 and 1000.0 Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels: 3.0 and 3.0 and 13.0 and 15.0 **Inclosure Type:** Encased **Functional Terminal Type And Quantity:** 1 friction w/grounding strap and pin input 1st function **Operating Voltage Rating And Type Per Function:** 125.0 volts ac blank and 200.0 volts dc blank **Body Material:** Metal Maximum Dielectric Withstanding Dc Voltage: 600.0 volts at sea level **Body Surface Treatment:** Gold **Precious Material And Location:** External surfaces gold **Precious Material:** Gold Style Designator: Round terminal/terminals on opposite surface **Specification Data:**

K0656-7057-2000 manufacturers source control

Radio Frequency Interference Filter - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0