

View Online at <https://aerobasegroup.com/nsn/5915-01-294-5782>

Vibration Resistance Range In Hertz:

+4.0/+50.0

Operating Temperature Range:

-28.0/+71.0 degrees celsius

Reference Frequency Per Function:

1.875 gigahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Voltage Standing Wave Ratio Per Function:

1.5 blank

Inclosure Type:

Encased

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Specified Frequencies Of Discrimination Per Function:

550.00 megahertz blank and 3.20 gigahertz blank and 4.00 gigahertz blank and 10.00 gigahertz blank

Frequency Band Width Per Function:

550.00 megahertz blank and 3.20 gigahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 3.0 blank and 60.0 blank and 60.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

550.0 megahertz blank and 3.2 gigahertz blank

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0