NSN 5915-01-294-9266

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-294-9266

Overall Height: 1.020 inches **Body Length:** Between 1.610 inches and 1.640 inches **Body Width:** Between 0.735 inches and 0.765 inches **Body Height:** 0.750 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 0.685 inches and 0.715 inches Vibration Resistance Range In Hertz: +4.0/+50.0 **Reference Frequency Per Function:** 45.0 megahertz blank **Source Impedance Rating Per Function:** 50.0 ohms blank **Load Impedance Per Function:** 50.0 ohms blank **Principal Circuitry Type Per Function:** Crystal blank **Voltage Standing Wave Ratio Per Function:** 1.5 blank **Mounting Facility Screw Thread Series Designator:** Unc **Inclosure Type:** Encased **Mounting Facility Type And Quantity:** 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 8.0 blank **Functional Terminal Type And Quantity:** 7 pin ground 3rd function **Specified Frequencies Of Discrimination Per Function:** 44.95 megahertz blank and 44.997 megahertz blank and 45.003 megahertz blank and 45.05 megahertz blank **Thread Size:** 0.086 inches **Body Material:** Metal **Frequency Band Width Per Function:** 44.997 megahertz blank and 45.003 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 3.0 blank and 60.0 blank

NSN 5915-01-294-9266

Band Pass Filter - Page 2 of 2



Voltage Standing Wave Ratio Frequency Limits Per Functio	Voltage	Standing	Wave Ratio	Frequency	Limits Per	Function
--	---------	----------	-------------------	-----------	------------	-----------------

44.997 megahertz blank and 45.003 megahertz blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0