

View Online at <https://aerobasegroup.com/nsn/5915-01-295-4511>

Overall Height:

Between 1.365 inches and 1.385 inches

Body Length:

Between 3.280 inches and 3.320 inches

Body Width:

Between 1.680 inches and 1.720 inches

Body Height:

Between 0.865 inches and 0.875 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.792 inches and 2.808 inches

Vibration Resistance Range In Hertz:

+20.0/+2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.192 inches and 1.208 inches

Operating Temperature Range:

-54.0/+85.0 degrees celsius

Reference Frequency Per Function:

340.5 kilohertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

4.0 blank

Functional Terminal Type And Quantity:

2 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

338.00 kilohertz blank and 339.50 kilohertz blank and 341.50 kilohertz blank and 343.00 kilohertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

339.50 kilohertz blank and 341.50 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

80.0 blank and 1.0 blank and 1.0 blank and 80.0 blank

Maximum Dielectric Withstanding Dc Voltage:

100.0 volts at sea level

Unpackaged Unit Weight:

0.450 pounds

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A047b0