NSN 5915-01-295-8471

High Pass Filter - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5915-01-295-8471 | |
|--|--|
| Overall Height: | |
| 1.200 inches | |
| Body Length: | |
| 3.000 inches | |
| Body Width: | |
| 2.000 inches | |
| Body Height: | |
| 1.000 inches | |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: | |
| 2.000 inches | |
| Operating Tempurature Range: | |
| +0.0/+70.0 degrees celsius | |
| End Application: | |
| Test unit, acoustic ts-4144/p | |
| Reference Frequency Per Function: | |
| 2.2 kilohertz blank | |
| Source Impedance Rating Per Function: | |
| 150.0 ohms blank | |
| Load Impedance Per Function: | |
| 150.0 ohms blank | |
| Principal Circuitry Type Per Function: | |
| Inductance-capacitance blank | |
| Mounting Facility Screw Thread Series Designator: | |
| Unc | |
| Inclosure Type: | |
| Encased | |
| Mounting Facility Type And Quantity: | |
| 2 threaded hole | |
| Insertion Loss At Reference Frequency Per Function In Decibels: | |
| 0.8 blank | |
| Functional Terminal Type And Quantity: | |
| 1 pin output 2nd function | |
| Specified Frequencies Of Discrimination Per Function: | |

40.00 hertz blank and 200.00 hertz blank and 400.00 hertz blank and 4.00 kilohertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

400.00 hertz blank and 4.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

51.56 blank and 75.55 blank and 3.0 blank and 1.0 blank

Special Features:

Active highpass filter; two 15vdc supply (+v, -v) and one offset voltage adjustment (os1) terminals

NSN 5915-01-295-8471

High Pass Filter - Page 2 of 2



Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0