## NSN 5915-01-295-8472

High Pass Filter - Page 1 of 2



| Thigh Fadd Fillion Fago For 2  |
|--|
| View Online at https://aerobasegroup.com/nsn/5915-01-295-8472                |
| Overall Height:  |
| 1.200 inches   |
| Body Length:   |
| 3.000 inches   |
| Body Width:  |
| 2.000 inches   |
| Body Height:   |
| 1.000 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 2.000 inches   |
| Operating Tempurature Range:   |
| +0.0/+70.0 degrees celsius   |
| End Application:   |
| Test unit, acoustic ts-4144/p  |
| Reference Frequency Per Function:  |
| 220.0 hertz blank  |
| Source Impedance Rating Per Function:  |
| 150.0 ohms blank   |
| Load Impedance Per Function:   |
| 150.0 ohms blank   |
| Principal Circuitry Type Per Function:                                       |
| Inductance-capacitance blank   |
| Mounting Facility Screw Thread Series Designator:                            |
| Unc  |
| Inclosure Type:  |
| Encased  |
| Mounting Facility Type And Quantity:   |
| 2 threaded hole  |
|  |

Insertion Loss At Reference Frequency Per Function In Decibels:

0.08 blank

**Functional Terminal Type And Quantity:** 

1 pin output 2nd function

**Specified Frequencies Of Discrimination Per Function:** 

4.00 hertz blank and 20.00 hertz blank and 40.00 hertz blank and 400.00 hertz blank

**Thread Size:** 

0.138 inches

**Frequency Band Width Per Function:** 

40.00 hertz blank and 400.00 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

51.56 blank and 75.55 blank and 3.0 blank and 1.0 blank

**Special Features:** 

Active highpass filter; two 15vdc supply (+v, -v) and one offset voltage adjustment (os1) terminals

## NSN 5915-01-295-8472

High Pass Filter - Page 2 of 2



| Style | Design | ator: |
|-------|--------|-------|
|-------|--------|-------|

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0