

View Online at <https://aerobasegroup.com/nsn/5915-01-296-2200>

Overall Height:

1.265 inches

Body Length:

Between 2.980 inches and 3.020 inches

Body Width:

Between 1.480 inches and 1.520 inches

Body Height:

0.875 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.692 inches and 2.708 inches

Vibration Resistance Range In Hertz:

+5.0/+2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.192 inches and 1.208 inches

Operating Temperature Range:

-54.0/+105.0 degrees celsius

Reference Frequency Per Function:

37.0 kilohertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

330.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

2 pin output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

100.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

1.50 kilohertz blank and 14.00 kilohertz blank and 60.00 kilohertz blank and 340.50 kilohertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

14.00 kilohertz blank and 60.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

30.0 blank and 1.0 blank and 1.0 blank and 40.0 blank

Body Surface Treatment:

Tin

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0