

View Online at <https://aerobasegroup.com/nsn/5915-01-296-2204>

**Overall Height:**

1.275 inches

**Body Length:**

Between 1.980 inches and 2.020 inches

**Body Width:**

Between 1.680 inches and 1.720 inches

**Body Height:**

0.875 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 1.692 inches and 1.708 inches

**Vibration Resistance Range In Hertz:**

+5.0/+2000.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 1.392 inches and 1.408 inches

**Operating Temperature Range:**

-54.0/+105.0 degrees celsius

**Reference Frequency Per Function:**

105.0 kilohertz blank

**Source Impedance Rating Per Function:**

3.48 kilohms blank

**Load Impedance Per Function:**

1.48 kilohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded hole

**Features Provided:**

Moisture resistant and shock resistant

**Insertion Loss At Reference Frequency Per Function In Decibels:**

0.9 blank

**Functional Terminal Type And Quantity:**

2 pin output 2nd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

50.0 volts at sea level

**Specified Frequencies Of Discrimination Per Function:**

1.00 hertz blank and 210.00 kilohertz blank and 1.00 megahertz blank and 10.00 megahertz blank

**Thread Size:**

0.112 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.00 hertz blank and 210.00 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 3.0 blank and 40.0 blank and 40.0 blank

**Body Surface Treatment:**

Tin

**Unpackaged Unit Weight:**

0.300 pounds

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0