

View Online at <https://aerobasegroup.com/nsn/5915-01-299-6313>

Overall Length:

0.518 inches

Body Outside Diameter:

0.062 inches

Unthreaded Mounting Hole Diameter:

Between 0.123 inches and 0.130 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.062 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.062 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Average Life Rating In Hours:

1000.0

End Application:

1520-01-125-5476 helicopter, observation

Source Impedance Rating Per Function:

50.0 ohms 4th radio interference

Load Impedance Per Function:

50.0 ohms 5th radio interference

Power Line Frequency Rating Per Function In Hertz:

60.0 3rd radio interference

Operating Current Rating Per Function In Amps:

5.0 3rd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 6th radio interference

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 unthreaded hole

Functional Terminal Type And Quantity:

35 friction w/grounding strap and pin output 2nd function

Operating Voltage Rating And Type Per Function:

120.0 volts ac 6th radio interference 6th function and 200.0 volts dc 6th radio interference 6th function

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

500.0 volts at sea level

Body Surface Treatment:

Gold

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Style Designator:

Round terminal/terminals on opposite surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0