

View Online at <https://aerobasegroup.com/nsn/5915-01-305-6240>

Overall Length:

1.451 inches

Body Length:

Between 0.860 inches and 0.880 inches

Body Outside Diameter:

Between 0.344 inches and 0.406 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Power Line Frequency Rating Per Function In Hertz:

400.0 blank

Operating Current Rating Per Function In Amps:

5.0 blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Full Load Insertion Loss Frequencies In Megahertz:

0.3 and 0.5 and 1.0 and 10.0 and 1000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

12.0 and 40.0 and 58.0 and 80.0 and 80.0

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

1 threaded bushing

Features Provided:

Nut and washer

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Operating Voltage Rating And Type Per Function:

115.0 volts ac blank and 200.0 volts dc blank

Thread Size:

0.250 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

400.0 volts at sea level

Body Surface Treatment:

Tin

Thread Tolerance Class:

2a external

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0