

View Online at <https://aerobasegroup.com/nsn/5915-01-306-9626>

Overall Length:

3.210 inches

Body Length:

2.380 inches

Body Width:

1.000 inches

Body Height:

1.060 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.940 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.560 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Reference Frequency Per Function:

21.4 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Input Terminal Manufacturer Code:

50140

Input Terminal Identification:

Sma receptacle

Voltage Standing Wave Ratio Per Function:

1.5 single band pass

Average Power Rating Per Function:

15.0 watts blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 threaded hole

Features Provided:

Moisture resistant and shock resistant

Insertion Loss At Reference Frequency Per Function In Decibels:

2.95 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Specified Frequencies Of Discrimination Per Function:

15.40 megahertz blank and 19.90 megahertz blank and 22.90 megahertz blank and 27.40 megahertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

19.90 megahertz blank and 22.90 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 1.0 blank and 1.0 blank and 58.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

19.9 megahertz blank and 22.9 megahertz blank

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0