

View Online at <https://aerobasegroup.com/nsn/5915-01-308-5414>

Overall Height:

Between 0.520 inches and 0.600 inches

Body Length:

Between 0.730 inches and 0.770 inches

Body Width:

Between 0.420 inches and 0.460 inches

Body Height:

Between 0.290 inches and 0.330 inches

Reference Frequency Per Function:

60.0 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Voltage Standing Wave Ratio Per Function:

1.2 single band pass

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

1 threaded stud

Features Provided:

Time delay

Insertion Loss At Reference Frequency Per Function In Decibels:

2.0 blank

Functional Terminal Type And Quantity:

4 pin ground 3rd function

Specified Frequencies Of Discrimination Per Function:

20.00 megahertz blank and 100.00 megahertz blank and 460.00 megahertz blank and 1.60 gigahertz blank

Thread Size:

0.086 inches

Frequency Band Width Per Function:

20.00 megahertz blank and 100.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 75.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

55.0 megahertz blank and 65.0 megahertz blank

Precious Material And Location:

Base surface gold

Precious Material:

Gold

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0