

View Online at <https://aerobasegroup.com/nsn/5915-01-309-5930>

Overall Length:

Between 3.980 inches and 4.040 inches

Body Length:

Between 3.220 inches and 3.280 inches

Body Width:

Between 2.720 inches and 2.780 inches

Body Height:

Between 0.970 inches and 1.030 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.740 inches and 2.760 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.490 inches and 2.510 inches

Operating Temperature Range:

+0.0/+65.0 degrees celsius

End Application:

0r15723 tas

Reference Frequency Per Function:

1.875 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Input Terminal Manufacturer Code:

53711

Input Terminal Identification:

Sma-receptacle

Output Terminal Manufacturer Code:

53711

Output Terminal Identification:

Sma-receptacle

Voltage Standing Wave Ratio Per Function:

1.3 single band pass

Average Power Rating Per Function:

27.0 watts blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded hole

Features Provided:

Moisture resistant and shock resistant

Insertion Loss At Reference Frequency Per Function In Decibels:

0.4 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Thread Size:

0.112 inches

Body Material:

Metal

Body Surface Treatment:

Gold

Unpackaged Unit Weight:

0.100 pounds

Precious Material And Location:

Bottom surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0