

View Online at https://aerobasegroup.com/nsn/5915-01-310-6069

Overall Length:
3.740 inches
Body Length:
Between 2.720 inches and 2.780 inches
Body Width:
Between 2.720 inches and 2.780 inches
Body Height:
Between 3.970 inches and 4.030 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 2.240 inches and 2.260 inches
Operating Tempurature Range:
-55.0/+100.0 degrees celsius
End Application:
Т305а
Source Impedance Rating Per Function:
50.0 ohms 2nd radio interference
Load Impedance Per Function:
50.0 ohms 2nd radio interference
Power Line Frequency Rating Per Function In Hertz:
420.0 2nd radio interference
Operating Current Rating Per Function In Amps:
10.0 2nd radio interference
Maximum Voltage Drop Per Function:
0.5 volts ac 2nd radio interference
Principal Circuitry Type Per Function:
Inductance-capacitance 2nd radio interference
Input Terminal Manufacturer Code:
96906
Input Terminal Identification:
Ms3113h-12c-3p
Maximum Tempurature Rise:
25.0 degrees celsius
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
4 threaded hole
Functional Terminal Type And Quantity:
2 tab, solder lug output 2nd function
Operating Voltage Rating And Type Per Function:
230.0 volts ac 2nd radio interference 2nd function



**Thread Size:** 0.164 inches **Body Material:** Metal Maximum Dielectric Withstanding Dc Voltage: 1.0 kilovolts at sea level Body Surface Treatment: Tin **Special Features:** Consists of two filtered functions Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A047b0