

View Online at <https://aerobasegroup.com/nsn/5915-01-314-6361>

**Overall Height:**

2.937 inches

**Body Length:**

Between 1.594 inches and 1.719 inches

**Body Width:**

Between 1.157 inches and 1.219 inches

**Body Height:**

2.500 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 1.234 inches and 1.266 inches

**Vibration Resistance Range In Hertz:**

+10.0/+2000.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.734 inches and 0.766 inches

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

200.0 hertz blank

**Source Impedance Rating Per Function:**

600.0 ohms blank

**Load Impedance Per Function:**

600.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 threaded stud

**Features Provided:**

Moisture resistant and shock resistant

**Insertion Loss At Reference Frequency Per Function In Decibels:**

6.0 blank

**Functional Terminal Type And Quantity:**

1 tab, solder lug output 2nd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

500.0 volts at sea level

**Specified Frequencies Of Discrimination Per Function:**

1.00 hertz blank and 1.00 kilohertz blank and 1.50 kilohertz blank and 2.00 kilohertz blank

**Thread Size:**

0.138 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.00 hertz blank and 1.00 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

6.0 blank and 40.0 blank

**Unpackaged Unit Weight:**

9.000 ounces

**Style Designator:**

Rectangular terminal/terminals on one surface

**Test Data Document:**

81349-mil-f-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-f-18327/30 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0