NSN 5915-01-314-6361

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-314-6361

Overall Height:
2.937 inches
Body Length:
Between 1.594 inches and 1.719 inches
Body Width:
Between 1.157 inches and 1.219 inches
Body Height:
2.500 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Between 1.234 inches and 1.266 inches
Vibration Resistance Range In Hertz:
+10.0/+2000.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.734 inches and 0.766 inches
Average Life Rating In Hours:
10000.0
Reference Frequency Per Function:
200.0 hertz blank
Source Impedance Rating Per Function:
600.0 ohms blank
Load Impedance Per Function:
600.0 ohms blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 threaded stud
Features Provided:
Moisture resistant and shock resistant
Insertion Loss At Reference Frequency Per Function In Decibels:
6.0 blank
Functional Terminal Type And Quantity:
1 tab, solder lug output 2nd function
Maximum Dielectric Withstanding Ac Rms Voltage:
500.0 volts at sea level
Specified Frequencies Of Discrimination Per Function:
1.00 hertz blank and 1.00 kilohertz blank and 1.50 kilohertz blank and 2.00 kilohertz blank
Thread Size:
0.138 inches

NSN 5915-01-314-6361

Low Pass Filter - Page 2 of 2



Body Material:

Metal

Frequency Band Width Per Function:

1.00 hertz blank and 1.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

6.0 blank and 40.0 blank

Unpackaged Unit Weight:

9.000 ounces

Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

81349-mil-f-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-f-18327/30 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0