

View Online at <https://aerobasegroup.com/nsn/5915-01-316-1747>

Overall Length:

2.250 inches

Body Length:

1.750 inches

Body Width:

0.500 inches

Body Height:

0.400 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.573 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.312 inches

Operating Temperature Range:

+0.0/+50.0 degrees celsius

End Application:

Training set, countermeasures signals an/msr-t4

Reference Frequency Per Function:

190.0 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Input Terminal Manufacturer Code:

60656

Input Terminal Identification:

Sma-receptacle

Output Terminal Manufacturer Code:

60656

Output Terminal Identification:

Sma-receptacle

Voltage Standing Wave Ratio Per Function:

1.5 blank

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

4.0 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

170.00 megahertz blank and 180.00 megahertz blank and 200.00 megahertz blank and 210.00 megahertz blank

Thread Size:

0.060 inches

Body Material:

Aluminum

Frequency Band Width Per Function:

180.00 megahertz blank and 200.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 50.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

180.0 megahertz blank and 200.0 megahertz blank

Body Surface Treatment:

Nickel

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0