NSN 5915-01-316-1747

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-316-1747

Overall Length:
2.250 inches
Body Length:
1.750 inches
Body Width:
0.500 inches
Body Height:
0.400 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.573 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.312 inches
Operating Tempurature Range:
+0.0/+50.0 degrees celsius
End Application:
Training set, countermeasures signals an/msr-t4
Reference Frequency Per Function:
190.0 megahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Input Terminal Manufacturer Code:
60656
Input Terminal Identification:
Sma-receptacle
Output Terminal Manufacturer Code:
60656
Output Terminal Identification:
Sma-receptacle
Voltage Standing Wave Ratio Per Function:
1.5 blank
Mounting Facility Screw Thread Series Designator:
Unf
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 threaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
4.0 blank

NSN 5915-01-316-1747

Band Pass Filter - Page 2 of 2



Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

170.00 megahertz blank and 180.00 megahertz blank and 200.00 megahertz blank and 210.00 megahertz blank

Thread Size:

0.060 inches

Body Material:

Aluminum

Frequency Band Width Per Function:

180.00 megahertz blank and 200.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 50.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

180.0 megahertz blank and 200.0 megahertz blank

Body Surface Treatment:

Nickel

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

.

A047b0