

View Online at <https://aerobasegroup.com/nsn/5915-01-318-4447>

**Overall Length:**

4.020 inches

**Overall Height:**

Between 2.595 inches and 2.655 inches

**Body Length:**

Between 3.480 inches and 3.520 inches

**Body Width:**

Between 3.480 inches and 3.520 inches

**Body Height:**

Between 1.980 inches and 2.020 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 2.990 inches and 3.010 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 2.990 inches and 3.010 inches

**Operating Temperature Range:**

-55.0/+100.0 degrees celsius

**Source Impedance Rating Per Function:**

50.0 ohms 2nd radio interference

**Load Impedance Per Function:**

50.0 ohms 2nd radio interference

**Power Line Frequency Rating Per Function In Hertz:**

400.0 2nd radio interference

**Operating Current Rating Per Function In Amps:**

8.0 2nd radio interference

**Maximum Voltage Drop Per Function:**

1.0 volts ac 1st radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 2nd radio interference

**Input Terminal Manufacturer Code:**

81349

**Input Terminal Identification:**

Ms3443h12c3pn

**Maximum Temperature Rise:**

25.0 degrees celsius

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded hole

**Functional Terminal Type And Quantity:**

2 tab, solder lug output 2nd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

1000.0 volts at sea level

**Operating Voltage Rating And Type Per Function:**

115.0 volts ac 2nd radio interference 2nd function

**Thread Size:**

0.164 inches

**Body Material:**

Metal

**Body Surface Treatment:**

Tin

**Style Designator:**

Rectangular terminal/terminals on two surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0