

View Online at <https://aerobasegroup.com/nsn/5915-01-319-5705>

**Overall Length:**

10.434 inches

**Mounting Slot Width:**

Between 0.286 inches and 0.295 inches

**Body Length:**

8.030 inches

**Body Width:**

8.030 inches

**Body Height:**

2.750 inches

**Vibration Resistance Range In Hertz:**

+5.0/+33.0

**Operating Temperature Range:**

+0.0/+65.0 degrees celsius

**End Application:**

G225100

**Source Impedance Rating Per Function:**

50.0 ohms 4th radio interference

**Load Impedance Per Function:**

50.0 ohms 5th radio interference

**Power Line Frequency Rating Per Function In Hertz:**

62.0 6th radio interference

**Operating Current Rating Per Function In Amps:**

15.0 3rd radio interference

**Maximum Voltage Drop Per Function:**

1.0 volts ac 6th radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 6th radio interference

**Input Terminal Manufacturer Code:**

96906

**Input Terminal Identification:**

Ms3406d24-2s

**Mounting Facility Screw Thread Series Designator:**

Unf

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 threaded hole

**Features Provided:**

Nut and washer

**Functional Terminal Type And Quantity:**

6 threaded stud output 2nd function

**Operating Voltage Rating And Type Per Function:**

115.0 volts ac 6th radio interference 6th function and 135.0 volts dc 6th radio interference 6th function

**Thread Size:**

0.190 inches

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

1.0 kilovolts at sea level

**Special Features:**

Six filtered functions

**Unpackaged Unit Weight:**

16.000 pounds

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0