

View Online at <https://aerobasegroup.com/nsn/5915-01-319-5705>

Overall Length:

10.434 inches

Mounting Slot Width:

Between 0.286 inches and 0.295 inches

Body Length:

8.030 inches

Body Width:

8.030 inches

Body Height:

2.750 inches

Vibration Resistance Range In Hertz:

+5.0/+33.0

Operating Temperature Range:

+0.0/+65.0 degrees celsius

End Application:

G225100

Source Impedance Rating Per Function:

50.0 ohms 4th radio interference

Load Impedance Per Function:

50.0 ohms 5th radio interference

Power Line Frequency Rating Per Function In Hertz:

62.0 6th radio interference

Operating Current Rating Per Function In Amps:

15.0 3rd radio interference

Maximum Voltage Drop Per Function:

1.0 volts ac 6th radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 6th radio interference

Input Terminal Manufacturer Code:

96906

Input Terminal Identification:

Ms3406d24-2s

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Features Provided:

Nut and washer

Functional Terminal Type And Quantity:

6 threaded stud output 2nd function

Operating Voltage Rating And Type Per Function:

115.0 volts ac 6th radio interference 6th function and 135.0 volts dc 6th radio interference 6th function

Thread Size:

0.190 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

1.0 kilovolts at sea level

Special Features:

Six filtered functions

Unpackaged Unit Weight:

16.000 pounds

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0