## NSN 5915-01-320-3595

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-320-3595

Overall Height:
2.250 inches
Body Length:
4.000 inches
Body Width:
1.000 inches
Body Height:
1.500 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
3.620 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.620 inches
Reference Frequency Per Function:
1.7 7th radio interference two phase to three phase
Source Impedance Rating Per Function:
600.0 ohms 4th low pass
Load Impedance Per Function:
600.0 ohms 4th low pass
Principal Circuitry Type Per Function:
Inductance-capacitance 3rd low pass
Input Terminal Manufacturer Code:
53682
Input Terminal Identification:
Sma-receptacle
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 threaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
3.0 1st low pass
Functional Terminal Type And Quantity:
4 pin output 2nd function
Specified Frequencies Of Discrimination Per Function:
1.00 hertz 4th low pass and 3.40 kilohertz 4th low pass and 12.00 kilohertz 4th low pass and 24.00 kilohertz 4th low pass
Thread Size:
0.112 inches
Body Material:
Metal
Frequency Band Width Per Function:

1.00 hertz 2nd low pass and 3.40 kilohertz 2nd low pass

## NSN 5915-01-320-3595

Low Pass Filter - Page 2 of 2



Discrimination At Specificationified Frequencies Per Function In Decibels:
3.0 blank and 40.0 blank
Special Features:
Four filtered functions
Style Designator:
Rectangular terminal/terminals on opposite surfaces
Shelf Life:
N/a

Demilitarization:

**Unit Of Measure:** 

No

Fiig:

A047b0