

View Online at <https://aerobasegroup.com/nsn/5915-01-322-3891>

Overall Height:

1.080 inches

Body Length:

2.250 inches

Body Width:

0.750 inches

Body Height:

0.770 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.800 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.300 inches

Operating Temperature Range:

-55.0/+100.0 degrees celsius

End Application:

Walleye mark 18

Reference Frequency Per Function:

10.7 megahertz blank

Source Impedance Rating Per Function:

500.0 ohms blank

Load Impedance Per Function:

500.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 threaded stud

Features Provided:

Shock resistant

Insertion Loss At Reference Frequency Per Function In Decibels:

2.0 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

10.672 megahertz blank and 10.697 megahertz blank and 10.703 megahertz blank and 10.728 megahertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

10.697 megahertz blank and 10.703 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 70.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A047b0