

View Online at <https://aerobasegroup.com/nsn/5915-01-322-3891>

**Overall Height:**

1.080 inches

**Body Length:**

2.250 inches

**Body Width:**

0.750 inches

**Body Height:**

0.770 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.800 inches

**Vibration Resistance Range In Hertz:**

+10.0/+2000.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.300 inches

**Operating Temperature Range:**

-55.0/+100.0 degrees celsius

**End Application:**

Walleye mark 18

**Reference Frequency Per Function:**

10.7 megahertz blank

**Source Impedance Rating Per Function:**

500.0 ohms blank

**Load Impedance Per Function:**

500.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 threaded stud

**Features Provided:**

Shock resistant

**Insertion Loss At Reference Frequency Per Function In Decibels:**

2.0 blank

**Functional Terminal Type And Quantity:**

1 pin output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

10.672 megahertz blank and 10.697 megahertz blank and 10.703 megahertz blank and 10.728 megahertz blank

**Thread Size:**

0.112 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

10.697 megahertz blank and 10.703 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 70.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A047b0