

View Online at <https://aerobasegroup.com/nsn/5915-01-323-6826>

**Overall Length:**

11.740 inches

**Body Length:**

3.370 inches

**Body Width:**

3.000 inches

**Body Height:**

2.250 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

3.000 inches

**Vibration Resistance Range In Hertz:**

+10.0/+500.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

2.625 inches

**Operating Temperature Range:**

-15.0/+55.0 degrees celsius

**Source Impedance Rating Per Function:**

50.0 ohms 2nd radio interference

**Load Impedance Per Function:**

50.0 ohms 2nd radio interference

**Power Line Frequency Rating Per Function In Hertz:**

60.0 2nd radio interference

**Operating Current Rating Per Function In Amps:**

3.0 2nd radio interference

**Maximum Voltage Drop Per Function:**

11.5 volts ac 2nd radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 2nd radio interference

**Input Terminal Manufacturer Code:**

13222

**Input Terminal Identification:**

Ms3124e12-3p

**Maximum Temperature Rise:**

20.0 degrees celsius

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 threaded hole

**Features Provided:**

Shock resistant

**Functional Terminal Type And Quantity:**

2 wire lead input 1st function

**Operating Voltage Rating And Type Per Function:**

115.0 volts ac 2nd radio interference 2nd function

**Thread Size:**

0.164 inches

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

200.0 volts at sea level

**Body Surface Treatment:**

Tin

**Special Features:**

Wire leads with receptacle connector

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0