

View Online at https://aerobasegroup.com/nsn/5915-01-324-2673

Overall Length:
1.197 inches
Body Length:
0.540 inches
Body Outside Diameter:
0.416 inches
Vibration Resistance Range In Hertz:
+10.0/+2000.0
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Average Life Rating In Hours:
1000.0
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Operating Current Rating Per Function In Amps:
1.0 blank
Maximum Voltage Drop Per Function:
140.0 millivolts dc blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Maximum Tempurature Rise:
25.0 degrees celsius
Mounting Facility Screw Thread Series Designator:
Unf
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
1 threaded bushing
Functional Terminal Type And Quantity:
1 tab, solder lug output 2nd function
Operating Voltage Rating And Type Per Function:
150.0 volts dc blank
Thread Size:
0.250 inches
Maximum Dielectric Withstanding Dc Voltage:
375.0 volts at sea level
Style Designator:
Round terminal/terminals on opposite surfaces
Test Data Document:
81349-mil-f-15733 specification (includes engineering type bulletins, brochures, etc., that refle

81349-mil-f-15733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).



Specification Data:

81349-mil-f-15733/23 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A047b0