

View Online at <https://aerobasegroup.com/nsn/5915-01-324-9560>

**Overall Height:**

0.625 inches

**Body Length:**

2.000 inches

**Body Width:**

0.550 inches

**Body Height:**

0.500 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.600 inches

**Vibration Resistance Range In Hertz:**

+5.0/+500.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.240 inches

**Operating Temperature Range:**

-55.0/+100.0 degrees celsius

**Reference Frequency Per Function:**

15.36 megahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Voltage Standing Wave Ratio Per Function:**

1.5 blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 threaded hole

**Features Provided:**

Moisture resistant and shock resistant

**Insertion Loss At Reference Frequency Per Function In Decibels:**

6.0 blank

**Functional Terminal Type And Quantity:**

1 pin output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

10.24 megahertz blank and 15.16 megahertz blank and 15.56 megahertz blank and 20.48 megahertz blank

**Thread Size:**

0.086 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

15.16 megahertz blank and 15.56 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 70.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

15.16 megahertz blank and 15.56 megahertz blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0