

View Online at <https://aerobasegroup.com/nsn/5915-01-324-9560>

Overall Height:

0.625 inches

Body Length:

2.000 inches

Body Width:

0.550 inches

Body Height:

0.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.600 inches

Vibration Resistance Range In Hertz:

+5.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.240 inches

Operating Temperature Range:

-55.0/+100.0 degrees celsius

Reference Frequency Per Function:

15.36 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Voltage Standing Wave Ratio Per Function:

1.5 blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded hole

Features Provided:

Moisture resistant and shock resistant

Insertion Loss At Reference Frequency Per Function In Decibels:

6.0 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

10.24 megahertz blank and 15.16 megahertz blank and 15.56 megahertz blank and 20.48 megahertz blank

Thread Size:

0.086 inches

Body Material:

Metal

Frequency Band Width Per Function:

15.16 megahertz blank and 15.56 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 70.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

15.16 megahertz blank and 15.56 megahertz blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0