

View Online at <https://aerobasegroup.com/nsn/5915-01-325-1767>

Overall Length:

4.187 inches

Body Length:

Between 3.855 inches and 3.895 inches

Body Width:

Between 1.730 inches and 1.770 inches

Body Height:

Between 1.277 inches and 1.317 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.563 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.437 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Reference Frequency Per Function:

400.0 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Voltage Standing Wave Ratio Per Function:

3.0 blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded hole

Features Provided:

Moisture resistant and shock resistant

Insertion Loss At Reference Frequency Per Function In Decibels:

0.55 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

225.00 megahertz blank and 400.00 megahertz blank and 450.00 megahertz blank and 2.00 gigahertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

225.00 megahertz blank and 400.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

0.5 blank and 65.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

225.0 megahertz blank and 400.0 megahertz blank

Special Features:

Two sma type connector receptacles

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0