

View Online at <https://aerobasegroup.com/nsn/5915-01-325-2835>

**Overall Height:**

4.130 inches

**Body Length:**

1.400 inches

**Body Width:**

0.600 inches

**Body Height:**

3.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.140 inches

**Vibration Resistance Range In Hertz:**

+10.0/+2000.0

**Operating Temperature Range:**

-54.0/+71.0 degrees celsius

**Reference Frequency Per Function:**

7.595 gigahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Input Terminal Manufacturer Code:**

53294

**Input Terminal Identification:**

Sma-receptacle

**Output Terminal Manufacturer Code:**

53294

**Output Terminal Identification:**

Sma-plug

**Voltage Standing Wave Ratio Per Function:**

1.5 blank

**Average Power Rating Per Function:**

0.1 watts blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

6 threaded hole

**Features Provided:**

Shock resistant

**Insertion Loss At Reference Frequency Per Function In Decibels:**

1.8 blank

**Functional Terminal Type And Quantity:**

1 connector, receptacle input 1st function

**Specified Frequencies Of Discrimination Per Function:**

7.315 gigahertz blank and 7.46 gigahertz blank and 7.73 gigahertz blank and 7.885 gigahertz blank

**Thread Size:**

0.112 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

7.46 gigahertz blank and 7.73 gigahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 30.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

7.46 gigahertz blank and 7.73 gigahertz blank

**Unpackaged Unit Weight:**

5.000 ounces

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0